Product Information for Z Series Work Desk System



Product Characteristics

- Distinctive four-leg frame with round or square tubular legs
- Several desks can be joined together with a mounting plate (powder-coated sheet steel, $120 \times 60 \times 2.5$ mm) that is screwed together with the desk top
- Fixed height (720 mm) or height-adjustable (650 850 mm)
- Desk depths: 600/800/900/1,000 mm
- Desk widths: 800 bis 2,000 mm
- Desk top thickness: 19 oder 25 mm

Frame

- All ophelis desk systems meet the requirements of the new EN 527 standard for office desks
- Round or square tubular legs
- Round tubular leg: 45 mm diameter
- Square tubular leg: 40 x 40 mm
- Inner frame
- The frame comprises the components panel frame, node connectors and legs
- Node connectors secure the panel frame
- Panel frame made of square tubing (powder-coated steel, 40 x 28 x 1.5 mm)
- The frame components are made of high-quality cast aluminium and drawn steel tubing.

Height adjustment

- Two versions:
 - · fixed desk height of 720 mm, with adjustment screw to adjust for uneven
- · Continuous height adjustment from 650 to 850 mm
- The desk height setting can be seen from the height markings on the inside of the leg

Electrification

- Horizontal: removable cable channel in the form of a 1.5 mm thick, square-edged powder-coated sheet steel profile (U-shaped) with a cross-section of $200\,x\,71\,mm$ and widths of 520, 720, 920, 1,120, 1,320 and 1,520 mm
- No cable channel for desk widths of 800 mm
- Vertical: Cable channel in the form of a movable plastic chain (ABS) with an inner diameter of 60 mm
- Cable outlet, round or square
- Netbase for desks with a depth of 1,000
- Netbox (see page 25)

Additive Elements

- Connecting elements
- Desk extensions
 - · With plate or round/square leg
- Computer bracket incl. mounting plate
 - · Height adjustable from 307 to 532 mm
 - · Width adjustable from 78 to 220 mm
 - · Weight 2.8 kg
 - · For computers with a weight of up to 15 kg
- Rear panel
- Monitor swivel arm
- Desk lamp
- Netbox (see page 25)



All additive elements are available in the following mounting options:

- mounted on the left
- mounted on the right

Layout of Z Series

- 1 leg pipe
- 2 grooves
- 3 node connector
- 4 height adjustment screw
- 5 horizontal cable channel
- 6 desk top

